

# TECNO LINE

MODEL:

**Compact PLUS 2E**

Variant with:

- Air Quality Sensor      For environments with the presence of odors
- SMOKE sensor      For rooms with smoke
- White BOX (Standard)



Patent application n. PCT/IB2009/055827

## BIPOLAR IONIZATION FOR AIR TREATMENT & SANIFICATION WITH OZONE CONTROLLED

Environment volume (m <sup>3</sup> )	Min 55 — Max *350
Air flow (m <sup>3</sup> /h)	from 50 to 150
Ionization type	Bipolar with 2 units 370 mm type E
Ventilation	Axial—4 speed
Noise Level dB (A)	~ 50
Weight (Kg)	12.1 – 13.1 (inox)
Ionizing control	Automatic with Air Quality sensor & Adjustable sensitivity
Power consumption (W)	60
Dimension L/W/H (mm)	620/160/280
Supply voltage	230 V/ 1 /50 Hz
Air filtration type	G4
Remote control	2 channels

\* The values shown are purely indicative and should always be adjusted according to actual situations of use.

## INSTALLATION

Fixing	<ul style="list-style-type: none"> <li>• On the wall at a height of 1,8 mt.</li> </ul>
Maintenance	<ul style="list-style-type: none"> <li>• Axial fan cleaning once a year.*</li> <li>• Ionization tube cleaning every 6 months.*</li> <li>• G4 filter replacement every 6 months.*</li> <li>• Air Quality sensor calibration check every 5 years.*</li> </ul>

\* The values shown are purely indicative and should always be adjusted according to actual situations of use.  
Tubes replacement is recommended after 10000 operating hours.



# TECNO LINE

MODEL:

**Compact PLUS 2E**

Variant with:

- Air Quality Sensor            For environments with the presence of odors
- SMOKE sensor            For rooms with smoke
- White BOX (Standard)



Patent application n. PCT/IB2009/055827

## BENEFITS OF TECHNOLOGY

The “**Bipolar Controlled Ionization**” system patented by Periso SA guarantees better air quality, purifying it from harmful microorganisms and contaminants.

Thanks to a natural system of beneficial ions emission, it is possible to promote the **healthiness of the environment**, physical comfort and to improve respiratory activity.

The system is controlled by a **sensor** that is very sensitive to volatile organic compounds and suspended particulates. This enable the activation of effective oxygen clusters and the decomposition of many complex odorous molecules into simpler elements.

In this way the **proliferation** of microorganisms and molds is eliminated, thanks to the damage to their cell membrane.

**Food preservation** can be guaranteed as well thanks to the natural sanification system, without alter the organoleptic characteristics of food.

## FIELDS OF APPLICATION

- Health service sector
- Hotel and Catering sector
- Food industry sector
- Waste-treatment sector
- Air treatment sector

